
Installation Instructions
Photometry

Orion Single Emission PX-0378-GRI

Surface-mounted wall light IP54 Orion Single Emission LED 7.3W 3000K ON-OFF Grey 610.00





TECHNICAL FEATURES


IP54 IK07


Luminaire total power : 7.3W
Real lumens : 527
Nominal lumens : 610
Real lm/W : 72
Lens / reflector angle : SPOT 17°
UGR : <=16
Structure material : Aluminium
Structure finish : Grey
Diffuser material : Glass
Diffuser finish : Transparent

Voltage / frequency : 100-240V ~ 50/60Hz
Dimming protocol : ON-OFF
Power Factor : 0.50
Useful life : 36.000h L70B30
Warranty : 5 Years
Easily recyclable luminaire

LUMINOTECHNIC FEATURES

CRI: 80
MacAdam steps: 3
Photobiological risk: RG1
UGR
UGR crosswise: 13.7
UGR lengthwise: 13.3





Lampholder	Quantity	Light source power (W)	Correlated Colour Temperature (CCT)
LED	1	5.6W	3000K

LOGISTICS

Net weight (kg): 0.73
Packaged weight (kg): 0.84
Packaging: 140mm x 100mm x 160mm

10 Un

LIGHT APPLICATION



Image may not match reference. LEDS C4 reserves the right to amend any of the product's components. The data related to flux, power and colour temperature are subject to a tolerance of ±10%.

Luminaire
Code PX-0378-GRI
Name APLIQUE PROYECTOR
Measurem.
Code PX-0378-GRI
Name APLIQUE PROYECTOR


Luminaire Flux	526.76 lm	Luminaire Power	7.29 W	Efficacy	72.26 lm/W	Efficiency	100.00%
Lamps Flux	526.76 lm	Maximum value	6290.01 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical


Round Luminaire	Diam. 90 mm	Height	140 mm
Round Luminous Area	Diam. 70 mm	Height	0 mm
Horizontal Luminous Area	0.003848 m2	Emitting area on Plane 180°	0.000000 m2
Emitting area on Plane 0°	0.000000 m2	Emitting area on Plane 270°	0.000000 m2
Emitting area on Plane 90°	0.000000 m2	Glare area at 76°	0.000931 m2
Coordinate system	CG	Symmetry Type	Double Symmetrical
Date	04-08-2017	Maximum Gamma Angle	90
Measurement Distance	0.00	Measurement Flux	526.76 lm
Operator	LEDS	Source Voltage [V]	
Temperature	25.00 °C	Source current [A]	
Humidity	60.00 %	Photocell	
Notes			

Luminaire Lamps

Line	Code	Name	Flux [lm]	Pow. [W]	Q.ty
	LED	LED	526.76	7.29	1

C.I.E.	97 99 100 100 100	D DIN 5040	A60
F UTE	--	B NBN	BZ 1





ULOR 0.00 %
DLOR100.00 %
RN 0.00 %

Luminaire
Code PX-0378-GRI
Name APLIQUE PROYECTOR
Measurem.
Code PX-0378-GRI
Name APLIQUE PROYECTOR

Luminaire Flux	526.76 lm	Luminaire Power	7.29 W	Efficacy	72.26 lm/W	Efficiency	100.00%
Lamps Flux	526.76 lm	Maximum value	6290.01 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical


Luminous Intensity Table cd/klm **Table 1/1**

	C 0.00	C 15.00	C 30.00	C 45.00	C 60.00	C 75.00	C 90.00
G 0.0	6290.01	6290.01	6290.01	6290.01	6290.01	6290.01	6290.01
G 5.0	4795.79	4758.33	4926.11	4859.06	5045.32	4860.97	5070.56
G 10.0	2385.82	2286.96	2422.02	2364.39	2469.97	2307.64	2502.90
G 15.0	895.89	844.00	891.05	842.26	932.91	862.07	915.19
G 20.0	405.05	400.54	421.58	414.38	423.08	413.85	419.56
G 25.0	341.00	343.40	341.99	342.31	344.59	344.06	339.26
G 30.0	318.11	322.33	312.90	315.70	314.45	316.17	315.44
G 35.0	171.89	182.24	188.89	188.72	179.81	181.90	170.92
G 40.0	23.40	23.22	24.19	24.62	25.14	24.97	25.78
G 45.0	16.97	16.69	17.29	17.39	17.76	17.84	18.09
G 50.0	12.60	12.59	12.79	12.98	13.07	13.03	13.17
G 55.0	9.93	9.86	10.00	10.01	10.02	9.79	9.92
G 60.0	8.56	8.52	8.55	8.46	8.38	8.19	8.17
G 65.0	7.49	7.44	7.44	7.29	7.12	6.76	6.85
G 70.0	6.01	6.01	5.99	5.69	5.57	5.29	5.18
G 75.0	4.18	4.16	4.08	3.90	3.59	3.27	3.21
G 80.0	2.33	2.24	2.19	1.80	1.70	1.45	1.50
G 85.0	0.83	0.85	0.78	0.63	0.52	0.31	0.26
G 90.0	0.06	0.06	0.07	0.08	0.08	0.06	0.02

Luminaire
Code PX-0378-GRI
Name APLIQUE PROYECTOR
Measurem.
Code PX-0378-GRI
Name APLIQUE PROYECTOR


Luminaire Flux	526.76 lm	Luminaire Power	7.29 W	Efficacy	72.26 lm/W	Efficiency	100.00%
Lamps Flux	526.76 lm	Maximum value	6290.01 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical

Diam=90mm



C Halfplanes





Luminaire
Code PX-0378-GRI
Name APLIQUE PROYECTOR
Measurem.
Code PX-0378-GRI
Name APLIQUE PROYECTOR


Luminaire Flux	526.76 lm	Luminaire Power	7.29 W	Efficacy	72.26 lm/W	Efficiency	100.00%
Lamps Flux	526.76 lm	Maximum value	6290.01 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.15	0.30	0.44	0.59	0.74	OC	0.15	0.31	0.46	0.62	0.77
OB	0.15	0.30	0.44	0.59	0.74	OD	0.15	0.31	0.46	0.62	0.77

Luminous Intensities [cd/klm]

	0	5	15	25	35	45	55	65	75	85
OA	3313.33	2526.23	471.92	179.62	90.54	8.94	5.23	3.94	2.20	0.44
OB	3313.33	2526.23	471.92	179.62	90.54	8.94	5.23	3.94	2.20	0.44
OC	3313.33	2670.97	482.08	178.71	90.03	9.53	5.23	3.61	1.69	0.14
OD	3313.33	2670.97	482.08	178.71	90.03	9.53	5.23	3.61	1.69	0.14



H[m]	D[m]	Max lux	Med lux	Alpha=8.4°+8.4° G=0.0
1.00	0.30	3313	2075	
2.00	0.59	828	519	
3.00	0.89	368	231	
4.00	1.18	207	130	
5.00	1.48	133	83	

H[m]	D[m]	Max lux	Med lux	Beta=8.7°+8.7° G=0.0
1.00	0.31	3313	2075	
2.00	0.62	828	519	
3.00	0.92	368	231	
4.00	1.23	207	130	
5.00	1.54	133	83	

Luminaire
Code PX-0378-GRI
Name APLIQUE PROYECTOR
Measurem.
Code PX-0378-GRI
Name APLIQUE PROYECTOR

Luminaire Flux	526.76 lm	Luminaire Power	7.29 W	Efficacy	72.26 lm/W	Efficiency	100.00%
Lamps Flux	526.76 lm	Maximum value	6290.01 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical


UGR
S = 0.250

Reflectancies										
Ceiling/Cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
WorkingPlane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
RoomDimensions	ViewedCrosswise					ViewedEndwise				
x=2H y=2H	12.9	13.6	13.1	13.8	13.8	12.8	13.4	13.0	13.6	13.8
x=2H y=3H	13.1	13.7	13.4	13.9	14.0	12.9	13.5	13.2	13.7	14.0
x=2H y=4H	13.2	13.8	13.5	14.0	14.0	13.0	13.5	13.3	13.8	14.0
x=2H y=6H	13.3	13.9	13.6	14.1	14.1	13.0	13.5	13.3	13.8	14.1
x=2H y=8H	13.3	13.8	13.7	14.1	14.0	13.0	13.5	13.3	13.8	14.0
x=2H y=12H	13.3	13.8	13.7	14.1	14.0	12.9	13.4	13.3	13.7	14.0
x=4H y=2H	12.8	13.4	13.2	13.7	13.8	12.7	13.3	13.0	13.5	13.8
x=4H y=3H	13.2	13.7	13.5	14.0	14.1	13.0	13.5	13.3	13.8	14.1
x=4H y=4H	13.4	13.8	13.8	14.2	14.2	13.1	13.5	13.5	13.9	14.2
x=4H y=6H	13.6	13.9	14.0	14.3	14.3	13.2	13.5	13.6	13.9	14.3
x=4H y=8H	13.6	13.9	14.0	14.3	14.2	13.2	13.4	13.6	13.8	14.2
x=4H y=12H	13.6	13.9	14.0	14.3	14.2	13.1	13.4	13.6	13.8	14.2
x=8H y=4H	13.4	13.7	13.9	14.1	14.2	13.2	13.4	13.6	13.8	14.2
x=8H y=6H	13.6	13.9	14.1	14.3	14.3	13.2	13.5	13.7	13.9	14.3
x=8H y=8H	13.7	13.9	14.2	14.3	14.3	13.2	13.4	13.7	13.9	14.3
x=8H y=12H	13.7	13.9	14.2	14.4	14.3	13.2	13.3	13.7	13.8	14.3
x=12H y=4H	13.4	13.7	13.8	14.1	14.2	13.1	13.4	13.6	13.8	14.2
x=12H y=6H	13.6	13.8	14.1	14.3	14.3	13.2	13.4	13.7	13.9	14.3
x=12H y=8H	13.7	13.8	14.2	14.3	14.3	13.2	13.4	13.7	13.8	14.3

Luminaire
Code PX-0378-GRI
Name APLIQUE PROYECTOR
Measurem.
Code PX-0378-GRI
Name APLIQUE PROYECTOR


Luminaire Flux	526.76 lm	Luminaire Power	7.29 W	Efficacy	72.26 lm/W	Efficiency	100.00%
Lamps Flux	526.76 lm	Maximum value	6290.01 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical

Diam=90mm



C Halfplanes


180.0 0.0
270.0 90.0



Luminaire
Code PX-0378-GRI
Name APLIQUE PROYECTOR
Measurem.
Code PX-0378-GRI
Name APLIQUE PROYECTOR

Luminaire Flux	526.76 lm	Luminaire Power	7.29 W	Efficacy	72.26 lm/W	Efficiency	100.00%
Lamps Flux	526.76 lm	Maximum value	6290.01 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical

Luminance



Luminaire
Code PX-0378-GRI
Name APLIQUE PROYECTOR
Measurem.
Code PX-0378-GRI
Name APLIQUE PROYECTOR

Luminaire Flux	526.76 lm	Luminaire Power	7.29 W	Efficacy	72.26 lm/W	Efficiency	100.00%
Lamps Flux	526.76 lm	Maximum value	6290.01 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical

Luminance cd/m2 **Table 1/3**

	C 0.00	C 10.00	C 20.00	C 30.00	C 40.00	C 50.00	C 60.00	C 70.00	C 80.00	C 90.00	C 100.00	C 110.00	C 120.00
G 0.0	861051.84	861051.84	861051.84	861051.84	861051.84	861051.84	861051.84	861051.84	861051.84	861051.84	861051.84	861051.84	861051.84
G 5.0	659012.85	651553.07	662053.19	676920.34	668633.28	676080.10	693301.74	675881.97	670520.83	696770.20	670520.83	675881.97	693301.74
G 10.0	331638.07	318281.97	323748.64	336669.14	330284.81	333672.44	343334.49	327095.79	323666.10	347911.89	323666.10	327095.79	343334.49
G 15.0	126966.09	120118.16	121960.17	126280.89	120365.42	123147.77	132212.91	125870.56	122157.86	129701.08	122157.86	125870.56	132212.91
G 20.0	59006.70	58067.52	59371.48	61414.93	60735.70	60659.08	61632.75	60776.64	60254.07	61121.01	60254.07	60776.64	61632.75
G 25.0	51505.33	51809.48	51833.15	51655.19	51633.80	51817.42	52047.57	52072.70	51778.19	51243.66	51778.19	52072.70	52047.57
G 30.0	50283.32	50999.09	50496.18	49459.70	49754.63	49913.75	49705.60	49868.98	49998.45	49861.10	49998.45	49868.98	49705.60
G 35.0	28725.19	29924.36	30907.26	31565.86	31778.95	31007.47	30049.47	30325.68	30060.35	28563.43	30060.35	30325.68	30049.47
G 40.0	4182.07	4136.22	4196.85	4322.06	4376.94	4435.73	4493.32	4466.76	4488.66	4606.01	4488.66	4466.76	4493.32
G 45.0	3285.37	3229.33	3263.08	3346.50	3361.35	3385.87	3437.69	3450.43	3464.14	3501.28	3464.14	3450.43	3437.69
G 50.0	2684.40	2678.31	2692.00	2723.18	2751.75	2773.66	2783.03	2776.15	2780.92	2805.52	2780.92	2776.15	2783.03
G 55.0	2369.87	2353.32	2362.87	2386.37	2388.37	2393.89	2391.91	2351.14	2336.19	2368.45	2336.19	2351.14	2391.91
G 60.0	2343.77	2334.76	2336.44	2339.65	2325.16	2310.47	2293.61	2256.91	2239.76	2236.62	2239.76	2256.91	2293.61
G 65.0	2425.82	2411.92	2409.15	2408.64	2377.71	2347.11	2305.87	2221.05	2184.07	2220.39	2184.07	2221.05	2305.87
G 70.0	2406.25	2405.80	2402.68	2396.89	2315.47	2257.42	2229.00	2153.41	2092.16	2073.17	2092.16	2153.41	2229.00
G 75.0	2209.99	2205.82	2191.84	2159.53	2101.87	2013.22	1896.59	1773.81	1719.28	1698.89	1719.28	1773.81	1896.59
G 80.0	1837.98	1779.16	1755.27	1729.68	1517.60	1379.17	1340.08	1204.54	1131.49	1184.46	1131.49	1204.54	1340.08
G 85.0	1300.96	1340.30	1325.34	1228.18	1068.25	943.36	820.64	591.13	433.19	407.60	433.19	591.13	820.64
G 90.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

Luminaire
Code PX-0378-GRI
Name APLIQUE PROYECTOR
Measurem.
Code PX-0378-GRI
Name APLIQUE PROYECTOR

Luminaire Flux	526.76 lm	Luminaire Power	7.29 W	Efficacy	72.26 lm/W	Efficiency	100.00%
Lamps Flux	526.76 lm	Maximum value	6290.01 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical

Luminance cd/m2 **Table 2/3**

	C 130.00	C 140.00	C 150.00	C 160.00	C 170.00	C 180.00	C 190.00	C 200.00	C 210.00	C 220.00	C 230.00	C 240.00	C 250.00
G 0.0	861051.84	861051.84	861051.84	861051.84	861051.84	861051.84	861051.84	861051.84	861051.84	861051.84	861051.84	861051.84	861051.84
G 5.0	676080.10	668633.28	676920.34	662053.19	651553.07	659012.85	651553.07	662053.19	676920.34	668633.28	676080.10	693301.74	675881.97
G 10.0	333672.44	330284.81	336669.14	323748.64	318281.97	331638.07	318281.97	323748.64	336669.14	330284.81	333672.44	343334.49	327095.79
G 15.0	123147.77	120365.42	126280.89	121960.17	120118.16	126966.09	120118.16	121960.17	126280.89	120365.42	123147.77	132212.91	125870.56
G 20.0	60659.08	60735.70	61414.93	59371.48	58067.52	59006.70	58067.52	59371.48	61414.93	60735.70	60659.08	61632.75	60776.64
G 25.0	51817.42	51633.80	51655.19	51833.15	51809.48	51505.33	51809.48	51833.15	51655.19	51633.80	51817.42	52047.57	52072.70
G 30.0	49913.75	49754.63	49459.70	50496.18	50999.09	50283.32	50999.09	50496.18	49459.70	49754.63	49913.75	49705.60	49868.98
G 35.0	31007.47	31778.95	31565.86	30907.26	29924.36	28725.19	29924.36	30907.26	31565.86	31778.95	31007.47	30049.47	30325.68
G 40.0	4435.73	4376.94	4322.06	4196.85	4136.22	4182.07	4136.22	4196.85	4322.06	4376.94	4435.73	4493.32	4466.76
G 45.0	3385.87	3361.35	3346.50	3263.08	3229.33	3285.37	3229.33	3263.08	3346.50	3361.35	3385.87	3437.69	3450.43
G 50.0	2773.66	2751.75	2723.18	2692.00	2678.31	2684.40	2678.31	2692.00	2723.18	2751.75	2773.66	2783.03	2776.15
G 55.0	2393.89	2388.37	2386.37	2362.87	2353.32	2369.87	2353.32	2362.87	2386.37	2388.37	2393.89	2391.91	2351.14
G 60.0	2310.47	2325.16	2339.65	2336.44	2334.76	2343.77	2334.76	2336.44	2339.65	2325.16	2310.47	2293.61	2256.91
G 65.0	2347.11	2377.71	2408.64	2409.15	2411.92	2425.82	2411.92	2409.15	2408.64	2377.71	2347.11	2305.87	2221.05
G 70.0	2257.42	2315.47	2396.89	2402.68	2405.80	2406.25	2405.80	2402.68	2396.89	2315.47	2257.42	2229.00	2153.41
G 75.0	2013.22	2101.87	2159.53	2191.84	2205.82	2209.99	2205.82	2191.84	2159.53	2101.87	2013.22	1896.59	1773.81
G 80.0	1379.17	1517.60	1729.68	1755.27	1779.16	1837.98	1779.16	1755.27	1729.68	1517.60	1379.17	1340.08	1204.54
G 85.0	943.36	1068.25	1228.18	1325.34	1340.30	1300.96	1340.30	1325.34	1228.18	1068.25	943.36	820.64	591.13
G 90.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

Luminaire
Code PX-0378-GRI
Name APLIQUE PROYECTOR
Measurem.
Code PX-0378-GRI
Name APLIQUE PROYECTOR

Luminaire Flux	526.76 lm	Luminaire Power	7.29 W	Efficacy	72.26 lm/W	Efficiency 100.00%
Lamps Flux	526.76 lm	Maximum value	6290.01 cd/klm	Position	C=0.00 G=0.00	CG Double Symmetrical

Luminance cd/m2 **Table 3/3**


	C 260.00	C 270.00	C 280.00	C 290.00	C 300.00	C 310.00	C 320.00	C 330.00	C 340.00	C 350.00
G 0.0	861051.84	861051.84	861051.84	861051.84	861051.84	861051.84	861051.84	861051.84	861051.84	861051.84
G 5.0	670520.83	696770.20	670520.83	675881.97	693301.74	676080.10	668633.28	676920.34	662053.19	651553.07
G 10.0	323666.10	347911.89	323666.10	327095.79	343334.49	333672.44	330284.81	336669.14	323748.64	318281.97
G 15.0	122157.86	129701.08	122157.86	125870.56	132212.91	123147.77	120365.42	126280.89	121960.17	120118.16
G 20.0	60254.07	61121.01	60254.07	60776.64	61632.75	60659.08	60735.70	61414.93	59371.48	58067.52
G 25.0	51778.19	51243.66	51778.19	52072.70	52047.57	51817.42	51633.80	51655.19	51833.15	51809.48
G 30.0	49998.45	49861.10	49998.45	49868.98	49705.60	49913.75	49754.63	49459.70	50496.18	50999.09
G 35.0	30060.35	28563.43	30060.35	30325.68	30049.47	31007.47	31778.95	31565.86	30907.26	29924.36
G 40.0	4488.66	4606.01	4488.66	4466.76	4493.32	4435.73	4376.94	4322.06	4196.85	4136.22
G 45.0	3464.14	3501.28	3464.14	3450.43	3437.69	3385.87	3361.35	3346.50	3263.08	3229.33
G 50.0	2780.92	2805.52	2780.92	2776.15	2783.03	2773.66	2751.75	2723.18	2692.00	2678.31
G 55.0	2336.19	2368.45	2336.19	2351.14	2391.91	2393.89	2388.37	2386.37	2362.87	2353.32
G 60.0	2239.76	2236.62	2239.76	2256.91	2293.61	2310.47	2325.16	2339.65	2336.44	2334.76
G 65.0	2184.07	2220.39	2184.07	2221.05	2305.87	2347.11	2377.71	2408.64	2409.15	2411.92
G 70.0	2092.16	2073.17	2092.16	2153.41	2229.00	2257.42	2315.47	2396.89	2402.68	2405.80
G 75.0	1719.28	1698.89	1719.28	1773.81	1896.59	2013.22	2101.87	2159.53	2191.84	2205.82
G 80.0	1131.49	1184.46	1131.49	1204.54	1340.08	1379.17	1517.60	1729.68	1755.27	1779.16
G 85.0	433.19	407.60	433.19	591.13	820.64	943.36	1068.25	1228.18	1325.34	1340.30
G 90.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

Luminaire
Code PX-0378-GRI
Name APLIQUE PROYECTOR
Measurem.
Code PX-0378-GRI
Name APLIQUE PROYECTOR

Luminaire Flux	526.76 lm	Luminaire Power	7.29 W	Efficacy	72.26 lm/W	Efficiency	100.00%
Lamps Flux	526.76 lm	Maximum value	6290.01 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical

PERCENTAGE ISOCANDLES

Projection: Equal Area SLI 10.8 Tight Tilting Angle:0°



Spread: 3.1° Narrow


Throw: 1.2° Short

Luminaire
Code PX-0378-GRI
Name APLIQUE PROYECTOR
Measurem.
Code PX-0378-GRI
Name APLIQUE PROYECTOR

Luminaire Flux	526.76 lm	Luminaire Power	7.29 W	Efficacy	72.26 lm/W	Efficiency	100.00%
Lamps Flux	526.76 lm	Maximum value	6290.01 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical

Isolux (Floor)

Luminaire position X=0.00m Y=0.00m Z=2.50m



Luminaire
Code PX-0378-GRI
Name APLIQUE PROYECTOR
Measurem.
Code PX-0378-GRI
Name APLIQUE PROYECTOR


Luminaire Flux	526.76 lm	Luminaire Power	7.29 W	Efficacy	72.26 lm/W	Efficiency	100.00%
Lamps Flux	526.76 lm	Maximum value	6290.01 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical

Average Luminance [cd/m²]

	45°	50°	55°	60°	65°	70°	75°	80°	85°	
0.0°	3285	2684	2370	2344	2426	2406	2210	1838	1301	---
90.0°	3501	2806	2368	2237	2220	2073	1699	1184	408	---


Flush mounted or longitudinal view


		Illumination(lx)										
A	A	2000	1000	750	500		<300					1.15
B	1		2000	1500	1000	750	500	<300				1.5
C					2000		1000	500	<300			1.85
D	2						2000	1000	500	<300		2.2
E	3							2000	1000	500	<300	2.55





Orion

PX-0378









03-11-2021