
Installation Instructions

Easy Square Surface 400mm

LedsC4 Team

TC-0414-BLA

Surface-mounted ceiling light Easy Square Surface 400mm IP23 LED 26.4W 4000K ON-OFF White 2300lm



TECHNICAL FEATURES

IP23

Luminaire total power : 29.3W

Real lumens : 2300

Nominal lumens : 3375

Real lm/W : 78

Lens / reflector angle : HORIZONTAL 113º

Structure material : Aluminium

Structure finish : White

Diffuser material : Acrylic

Diffuser finish : Opal

Voltage / frequency : 100-240V ~ 50/60Hz

Dimming protocol : ON-OFF

Power Factor : 0.90

Useful life : 36.000h L70B30

Warranty : 5 Years

Easily recyclable luminaire


LUMINOTECHNIC FEATURES


CRI: 80

MacAdam steps: 3

Photobiological risk: RG1

Lampholder	Quantity	Light source power (W)	Correlated Colour Temperature (CCT)
LED	1	26.4W	4000K





LOGISTICS

Net weight (kg): 1.47

Packaged weight (kg): 1.78

Packaging: 410mm x 410mm x 45mm

5 Un

Image may not match reference. LEDS C4 reserves the right to amend any of the product's components. The data related to flux, power and colour temperature are subject to a tolerance of ±10%.

Luminaire
Code TC-0414-BLA
Name PLAFÓN FORLIGHT LEDS
Measurem.
Code TC-0413-BLA
Name PLAFÓN FORLIGHT LEDS

Luminaire Flux	2300.41 lm	Luminaire Power	30.68 W	Efficacy	74.98 lm/W	Efficiency	100.00%
Lamps Flux	2300.41 lm	Maximum value	344.22 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical

Rectangular Luminaire		Length	400 mm	Width	400 mm	Height	35 mm
Rectangular Luminous Area		Length	354 mm	Width	354 mm	Height	0 mm
Horizontal Luminous Area		0.125316 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.030317 m2	

Coordinate system	CG	Symmetry Type	Double Symmetrical
Date	06-10-2017	Maximum Gamma Angle	90
Measurement Distance	0.00	Measurement Flux	2300.41 lm


Operator	Asselum T2	Source Voltage [V]	
Temperature	25.00 °C	Source current [A]	
Humidity	60.00 %	Photocell	
Notes			

Luminaire Lamps


Line	Code	Name	Flux [lm]	Pow. [W]	Q.ty
	TC-0414-BLA	TC-0414-BLA	2300.41	30.68	1

C.I.E.	47 79 95 100 100	D DIN 5040	A30
F UTE	1.00 E	B NBN	BZ 5

400mm x 400mm



C Halfplanes
180.0 — 0.0
270.0 — 90.0



ULOR 0.00 %
DLOR100.00 %
RN 0.00 %

Luminaire
Code TC-0414-BLA
Name PLAFÓN FORLIGHT LEDS
Measurem.
Code TC-0413-BLA
Name PLAFÓN FORLIGHT LEDS

Luminaire Flux	2300.41 lm	Luminaire Power	30.68 W	Efficacy	74.98 lm/W	Efficiency	100.00%
Lamps Flux	2300.41 lm	Maximum value	344.22 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical


Luminous Intensity Table cd/klm **Table 1/1**

	C 0.00	C 15.00	C 30.00	C 45.00	C 60.00	C 75.00	C 90.00
G 0.0	344.22	344.22	344.22	344.22	344.22	344.22	344.22
G 5.0	343.24	343.14	343.06	342.78	342.73	342.56	342.62
G 10.0	340.29	340.12	339.66	339.08	338.06	337.78	337.42
G 15.0	335.23	334.78	333.72	332.20	330.77	329.65	329.31
G 20.0	327.58	326.81	325.21	322.49	320.60	318.52	318.37
G 25.0	318.09	317.11	314.15	310.71	306.75	304.76	303.35
G 30.0	304.69	303.48	299.82	295.19	290.95	287.72	287.38
G 35.0	288.66	286.75	282.49	276.29	272.37	268.17	267.37
G 40.0	269.51	267.94	262.91	257.29	250.25	246.84	244.86
G 45.0	246.62	245.02	239.74	233.37	227.20	223.18	221.57
G 50.0	221.43	218.74	214.55	207.28	202.48	197.87	197.03
G 55.0	194.37	192.66	187.26	182.00	175.03	171.97	170.08
G 60.0	163.89	161.78	157.57	152.32	147.68	144.78	143.71
G 65.0	132.04	130.83	127.64	122.65	120.35	116.83	116.82
G 70.0	101.65	101.35	97.50	95.47	91.02	90.69	88.78
G 75.0	70.83	69.97	68.22	66.18	64.60	63.31	63.72
G 80.0	43.57	41.83	42.03	39.20	39.62	38.63	39.02
G 85.0	18.04	18.55	18.02	18.11	16.94	16.93	16.45
G 90.0	0.74	0.79	0.70	0.64	0.62	0.59	0.61

Luminaire
Code TC-0414-BLA
Name PLAFÓN FORLIGHT LEDS
Measurem.
Code TC-0413-BLA
Name PLAFÓN FORLIGHT LEDS

Luminaire Flux	2300.41 lm	Luminaire Power	30.68 W	Efficacy	74.98 lm/W	Efficiency	100.00%
Lamps Flux	2300.41 lm	Maximum value	344.22 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical


400mm x 400mm



C Halfplanes

180.0 0.0

270.0 90.0



Luminaire
Code TC-0414-BLA
Name PLAFÓN FORLIGHT LEDS
Measurem.
Code TC-0413-BLA
Name PLAFÓN FORLIGHT LEDS


Luminaire Flux	2300.41 lm	Luminaire Power	30.68 W	Efficacy	74.98 lm/W	Efficiency	100.00%
Lamps Flux	2300.41 lm	Maximum value	344.22 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical

Width at 50.00 % of Max Intensity


H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	1.64	3.29	4.93	6.58	8.22	OC	1.41	2.82	4.23	5.63	7.04
OB	1.64	3.29	4.93	6.58	8.22	OD	1.41	2.82	4.23	5.63	7.04

Luminous Intensities [cd/klm]


	0	5	15	25	35	45	55	65	75	85
OA	791.84	789.60	771.16	731.74	664.03	567.32	447.12	303.75	162.95	41.49
OB	791.84	789.60	771.16	731.74	664.03	567.32	447.12	303.75	162.95	41.49
OC	791.84	788.17	757.55	697.82	615.07	509.70	391.25	268.73	146.59	37.85
OD	791.84	788.17	757.55	697.82	615.07	509.70	391.25	268.73	146.59	37.85



H[m]	D[m]	Max lux	Med lux
1.00	3.29	792	190
2.00	6.58	198	47
3.00	9.87	88	21
4.00	13.16	49	12
5.00	16.44	32	8



H[m]	D[m]	Max lux	Med lux
1.00	2.82	792	190
2.00	5.63	198	47
3.00	8.45	88	21
4.00	11.27	49	12
5.00	14.08	32	8



Luminaire
Code TC-0414-BLA
Name PLAFÓN FORLIGHT LEDS
Measurem.
Code TC-0413-BLA
Name PLAFÓN FORLIGHT LEDS

Luminaire Flux	2300.41 lm	Luminaire Power	30.68 W	Efficacy	74.98 lm/W	Efficiency	100.00%
Lamps Flux	2300.41 lm	Maximum value	344.22 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical


UGR
S = 0.250

Reflectancies										
Ceiling/Cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
WorkingPlane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
RoomDimensions	ViewedCrosswise					ViewedEndwise				
x=2H y=2H	18.9	20.2	19.2	20.5	20.7	18.3	19.6	18.6	19.8	20.1
x=2H y=3H	20.6	21.8	20.9	22.0	22.3	19.9	21.1	20.2	21.3	21.6
x=2H y=4H	21.2	22.3	21.5	22.6	22.9	20.5	21.6	20.8	21.9	22.2
x=2H y=6H	21.7	22.8	22.1	23.1	23.4	21.0	22.1	21.4	22.4	22.7
x=2H y=8H	21.9	22.9	22.2	23.2	23.5	21.2	22.2	21.5	22.5	22.8
x=2H y=12H	22.0	22.9	22.3	23.3	23.6	21.3	22.2	21.6	22.6	22.9
x=4H y=2H	19.6	20.7	19.9	21.0	21.3	19.1	20.2	19.4	20.5	20.8
x=4H y=3H	21.4	22.4	21.8	22.7	23.1	20.9	21.8	21.2	22.2	22.5
x=4H y=4H	22.2	23.1	22.6	23.4	23.8	21.6	22.5	22.0	22.8	23.2
x=4H y=6H	22.8	23.6	23.2	24.0	24.4	22.2	23.0	22.7	23.4	23.8
x=4H y=8H	23.0	23.7	23.5	24.1	24.6	22.5	23.1	22.9	23.5	24.0
x=4H y=12H	23.2	23.8	23.6	24.2	24.7	22.6	23.2	23.1	23.6	24.1
x=8H y=4H	22.5	23.2	22.9	23.6	24.0	22.0	22.7	22.4	23.1	23.5
x=8H y=6H	23.3	23.8	23.7	24.3	24.7	22.8	23.3	23.2	23.8	24.2
x=8H y=8H	23.6	24.1	24.1	24.5	25.0	23.1	23.5	23.5	24.0	24.5
x=8H y=12H	23.8	24.2	24.3	24.7	25.2	23.3	23.7	23.8	24.2	24.7
x=12H y=4H	22.5	23.2	23.0	23.6	24.0	22.1	22.7	22.5	23.1	23.5
x=12H y=6H	23.3	23.8	23.8	24.3	24.8	22.8	23.3	23.3	23.8	24.3
x=12H y=8H	23.7	24.1	24.2	24.6	25.1	23.2	23.6	23.7	24.1	24.6

Luminaire
Code TC-0414-BLA
Name PLAFÓN FORLIGHT LEDS
Measurem.
Code TC-0413-BLA
Name PLAFÓN FORLIGHT LEDS


Luminaire Flux	2300.41 lm	Luminaire Power	30.68 W	Efficacy	74.98 lm/W	Efficiency	100.00%
Lamps Flux	2300.41 lm	Maximum value	344.22 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical

400mm x 400mm



C Halfplanes


180.0 0.0
270.0 90.0



Luminaire
Code TC-0414-BLA
Name PLAFÓN FORLIGHT LEDS
Measurem.
Code TC-0413-BLA
Name PLAFÓN FORLIGHT LEDS

Luminaire Flux	2300.41 lm	Luminaire Power	30.68 W	Efficacy	74.98 lm/W	Efficiency	100.00%
Lamps Flux	2300.41 lm	Maximum value	344.22 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical

Luminance



Luminaire
Code TC-0414-BLA
Name PLAFÓN FORLIGHT LEDS
Measurem.
Code TC-0413-BLA
Name PLAFÓN FORLIGHT LEDS

Luminaire Flux	2300.41 lm	Luminaire Power	30.68 W	Efficacy	74.98 lm/W	Efficiency 100.00%
Lamps Flux	2300.41 lm	Maximum value	344.22 cd/klm	Position	C=0.00 G=0.00	CG Double Symmetrical

Luminance cd/m2 **Table 1/3**

	C 0.00	C 10.00	C 20.00	C 30.00	C 40.00	C 50.00	C 60.00	C 70.00	C 80.00	C 90.00	C 100.00	C 110.00	C 120.00
G 0.0	6318.75	6318.75	6318.75	6318.75	6318.75	6318.75	6318.75	6318.75	6318.75	6318.75	6318.75	6318.75	6318.75
G 5.0	6324.90	6323.50	6322.84	6321.61	6317.96	6315.84	6315.42	6313.19	6312.16	6313.51	6312.16	6313.19	6315.42
G 10.0	6342.94	6341.49	6337.39	6331.25	6325.07	6313.93	6301.38	6297.10	6294.53	6289.51	6294.53	6297.10	6301.38
G 15.0	6370.79	6366.14	6357.08	6342.10	6323.07	6303.82	6286.16	6270.51	6261.35	6258.38	6261.35	6270.51	6286.16
G 20.0	6399.20	6390.14	6376.66	6352.91	6316.86	6286.51	6262.91	6233.35	6221.25	6219.38	6221.25	6233.35	6262.91
G 25.0	6442.82	6433.51	6406.36	6362.91	6318.16	6265.30	6213.00	6182.82	6163.29	6144.18	6163.29	6182.82	6213.00
G 30.0	6458.37	6445.81	6412.26	6355.28	6289.69	6225.89	6167.17	6115.60	6096.21	6091.40	6096.21	6115.60	6167.17
G 35.0	6468.66	6443.90	6401.72	6330.45	6234.69	6158.69	6103.61	6036.19	6003.58	5991.77	6003.58	6036.19	6103.61
G 40.0	6458.30	6441.46	6386.90	6300.11	6214.66	6107.91	5996.87	5934.06	5898.47	5867.63	5898.47	5934.06	5996.87
G 45.0	6402.33	6383.47	6324.18	6223.70	6114.12	6002.13	5898.23	5820.57	5775.10	5752.06	5775.10	5820.57	5898.23
G 50.0	6323.72	6273.71	6216.55	6127.23	5986.79	5867.41	5782.43	5687.45	5642.84	5626.76	5642.84	5687.45	5782.43
G 55.0	6220.53	6196.66	6115.96	5993.07	5886.22	5749.33	5601.71	5525.15	5483.64	5443.20	5483.64	5525.15	5601.71
G 60.0	6016.92	5971.95	5896.40	5784.84	5656.62	5530.48	5421.97	5342.49	5297.29	5276.23	5297.29	5342.49	5421.97
G 65.0	5735.38	5705.77	5650.01	5544.09	5391.06	5288.24	5227.49	5118.95	5074.58	5074.22	5074.58	5118.95	5227.49
G 70.0	5455.84	5444.88	5376.68	5233.05	5168.60	5045.06	4885.38	4873.34	4848.69	4765.19	4848.69	4873.34	4885.38
G 75.0	5023.89	4988.18	4927.72	4838.76	4739.78	4654.27	4581.50	4510.56	4488.44	4519.64	4488.44	4510.56	4581.50
G 80.0	4606.02	4451.95	4438.16	4443.11	4231.74	4132.40	4188.84	4123.14	4075.94	4125.04	4075.94	4123.14	4188.84
G 85.0	3799.14	3898.68	3874.31	3795.76	3825.18	3742.94	3568.80	3567.34	3551.40	3465.57	3551.40	3567.34	3568.80
G 90.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

Luminaire
Code TC-0414-BLA
Name PLAFÓN FORLIGHT LEDS
Measurem.
Code TC-0413-BLA
Name PLAFÓN FORLIGHT LEDS

Luminaire Flux	2300.41 lm	Luminaire Power	30.68 W	Efficacy	74.98 lm/W	Efficiency	100.00%
Lamps Flux	2300.41 lm	Maximum value	344.22 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical

Luminance cd/m2 **Table 2/3**

	C 130.00	C 140.00	C 150.00	C 160.00	C 170.00	C 180.00	C 190.00	C 200.00	C 210.00	C 220.00	C 230.00	C 240.00	C 250.00
G 0.0	6318.75	6318.75	6318.75	6318.75	6318.75	6318.75	6318.75	6318.75	6318.75	6318.75	6318.75	6318.75	6318.75
G 5.0	6315.84	6317.96	6321.61	6322.84	6323.50	6324.90	6323.50	6322.84	6321.61	6317.96	6315.84	6315.42	6313.19
G 10.0	6313.93	6325.07	6331.25	6337.39	6341.49	6342.94	6341.49	6337.39	6331.25	6325.07	6313.93	6301.38	6297.10
G 15.0	6303.82	6323.07	6342.10	6357.08	6366.14	6370.79	6366.14	6357.08	6342.10	6323.07	6303.82	6286.16	6270.51
G 20.0	6286.51	6316.86	6352.91	6376.66	6390.14	6399.20	6390.14	6376.66	6352.91	6316.86	6286.51	6262.91	6233.35
G 25.0	6265.30	6318.16	6362.91	6406.36	6433.51	6442.82	6433.51	6406.36	6362.91	6318.16	6265.30	6213.00	6182.82
G 30.0	6225.89	6289.69	6355.28	6412.26	6445.81	6458.37	6445.81	6412.26	6355.28	6289.69	6225.89	6167.17	6115.60
G 35.0	6158.69	6234.69	6330.45	6401.72	6443.90	6468.66	6443.90	6401.72	6330.45	6234.69	6158.69	6103.61	6036.19
G 40.0	6107.91	6214.66	6300.11	6386.90	6441.46	6458.30	6441.46	6386.90	6300.11	6214.66	6107.91	5996.87	5934.06
G 45.0	6002.13	6114.12	6223.70	6324.18	6383.47	6402.33	6383.47	6324.18	6223.70	6114.12	6002.13	5898.23	5820.57
G 50.0	5867.41	5986.79	6127.23	6216.55	6273.71	6323.72	6273.71	6216.55	6127.23	5986.79	5867.41	5782.43	5687.45
G 55.0	5749.33	5886.22	5993.07	6115.96	6196.66	6220.53	6196.66	6115.96	5993.07	5886.22	5749.33	5601.71	5525.15
G 60.0	5530.48	5656.62	5784.84	5896.40	5971.95	6016.92	5971.95	5896.40	5784.84	5656.62	5530.48	5421.97	5342.49
G 65.0	5288.24	5391.06	5544.09	5650.01	5705.77	5735.38	5705.77	5650.01	5544.09	5391.06	5288.24	5227.49	5118.95
G 70.0	5045.06	5168.60	5233.05	5376.68	5444.88	5455.84	5444.88	5376.68	5233.05	5168.60	5045.06	4885.38	4873.34
G 75.0	4654.27	4739.78	4838.76	4927.72	4988.18	5023.89	4988.18	4927.72	4838.76	4739.78	4654.27	4581.50	4510.56
G 80.0	4132.40	4231.74	4443.11	4438.16	4451.95	4606.02	4451.95	4438.16	4443.11	4231.74	4132.40	4188.84	4123.14
G 85.0	3742.94	3825.18	3795.76	3874.31	3898.68	3799.14	3898.68	3874.31	3795.76	3825.18	3742.94	3568.80	3567.34
G 90.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

Luminaire
Code TC-0414-BLA
Name PLAFÓN FORLIGHT LEDS
Measurem.
Code TC-0413-BLA
Name PLAFÓN FORLIGHT LEDS

Luminaire Flux	2300.41 lm	Luminaire Power	30.68 W	Efficacy	74.98 lm/W	Efficiency 100.00%
Lamps Flux	2300.41 lm	Maximum value	344.22 cd/klm	Position	C=0.00 G=0.00	CG Double Symmetrical

Luminance cd/m2 **Table 3/3**


	C 260.00	C 270.00	C 280.00	C 290.00	C 300.00	C 310.00	C 320.00	C 330.00	C 340.00	C 350.00
G 0.0	6318.75	6318.75	6318.75	6318.75	6318.75	6318.75	6318.75	6318.75	6318.75	6318.75
G 5.0	6312.16	6313.51	6312.16	6313.19	6315.42	6315.84	6317.96	6321.61	6322.84	6323.50
G 10.0	6294.53	6289.51	6294.53	6297.10	6301.38	6313.93	6325.07	6331.25	6337.39	6341.49
G 15.0	6261.35	6258.38	6261.35	6270.51	6286.16	6303.82	6323.07	6342.10	6357.08	6366.14
G 20.0	6221.25	6219.38	6221.25	6233.35	6262.91	6286.51	6316.86	6352.91	6376.66	6390.14
G 25.0	6163.29	6144.18	6163.29	6182.82	6213.00	6265.30	6318.16	6362.91	6406.36	6433.51
G 30.0	6096.21	6091.40	6096.21	6115.60	6167.17	6225.89	6289.69	6355.28	6412.26	6445.81
G 35.0	6003.58	5991.77	6003.58	6036.19	6103.61	6158.69	6234.69	6330.45	6401.72	6443.90
G 40.0	5898.47	5867.63	5898.47	5934.06	5996.87	6107.91	6214.66	6300.11	6386.90	6441.46
G 45.0	5775.10	5752.06	5775.10	5820.57	5898.23	6002.13	6114.12	6223.70	6324.18	6383.47
G 50.0	5642.84	5626.76	5642.84	5687.45	5782.43	5867.41	5986.79	6127.23	6216.55	6273.71
G 55.0	5483.64	5443.20	5483.64	5525.15	5601.71	5749.33	5886.22	5993.07	6115.96	6196.66
G 60.0	5297.29	5276.23	5297.29	5342.49	5421.97	5530.48	5656.62	5784.84	5896.40	5971.95
G 65.0	5074.58	5074.22	5074.58	5118.95	5227.49	5288.24	5391.06	5544.09	5650.01	5705.77
G 70.0	4848.69	4765.19	4848.69	4873.34	4885.38	5045.06	5168.60	5233.05	5376.68	5444.88
G 75.0	4488.44	4519.64	4488.44	4510.56	4581.50	4654.27	4739.78	4838.76	4927.72	4988.18
G 80.0	4075.94	4125.04	4075.94	4123.14	4188.84	4132.40	4231.74	4443.11	4438.16	4451.95
G 85.0	3551.40	3465.57	3551.40	3567.34	3568.80	3742.94	3825.18	3795.76	3874.31	3898.68
G 90.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

Luminaire
Code TC-0414-BLA
Name PLAFÓN FORLIGHT LEDS
Measurem.
Code TC-0413-BLA
Name PLAFÓN FORLIGHT LEDS

Luminaire Flux	2300.41 lm	Luminaire Power	30.68 W	Efficacy	74.98 lm/W	Efficiency	100.00%
Lamps Flux	2300.41 lm	Maximum value	344.22 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical

PERCENTAGE ISOCANDLES

Projection: SLI 6.4 Tight Tilting Angle:0°



Spread: 23.0° Narrow


Throw: 14.2° Short

Luminaire
Code TC-0414-BLA
Name PLAFÓN FORLIGHT LEDS
Measurem.
Code TC-0413-BLA
Name PLAFÓN FORLIGHT LEDS

Luminaire Flux	2300.41 lm	Luminaire Power	30.68 W	Efficacy	74.98 lm/W	Efficiency	100.00%
Lamps Flux	2300.41 lm	Maximum value	344.22 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical

Isolux (Floor)

Luminaire position X=0.00m Y=0.00m Z=2.50m



Luminaire
Code TC-0414-BLA
Name PLAFÓN FORLIGHT LEDS
Measurem.
Code TC-0413-BLA
Name PLAFÓN FORLIGHT LEDS


Luminaire Flux	2300.41 lm	Luminaire Power	30.68 W	Efficacy	74.98 lm/W	Efficiency	100.00%
Lamps Flux	2300.41 lm	Maximum value	344.22 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical


Average Luminance [cd/m²]

	45°	50°	55°	60°	65°	70°	75°	80°	85°	
0.0°	6402	6324	6221	6017	5735	5456	5024	4606	3799	---
90.0°	5752	5627	5443	5276	5074	4765	4520	4125	3466	---

Flush mounted or longitudinal view


		Illumination(lx)										
A	A	2000	1000	750	500		<300					1.15
B	1		2000	1500	1000	750	500	<300				1.5
C					2000		1000	500	<300			1.85
D	2						2000	1000	500	<300		2.2
E	3							2000	1000	500	<300	2.55









PLANTILLA DE INSTALACIÓN
INSTALLATION TEMPLATE



①



②



③

